

Ronacrete Rapid Primer

Rapid setting primer for fast setting cementitious products



FEATURES

- bonds new concrete to old
- provides a strong chemical bond
- multiple coats provide protection to steel
- easy to apply

Description

Ronacrete Rapid Primer is a prebagged cementitious bonding primer comprising polymer liquid and rapid setting cements. Ronacrete Rapid primer is used to provide a chemical bond between the substrate and new surfacing. It is only to be used with Ronacrete's rapid setting mortars and concretes including RonaBond HB40 Ultra Rapid, RonaFloor Repair 1 Hour, RonaScreed Mortar and RonaScreed Concrete.

Instructions for Use

Preparation

Mechanically prepare substrate in accordance with BS 8204 Part 3:1993. Provide structurally sound and clean substrate to receive high strength mortar / concrete. Damp the surface with potable water and apply to the damp surface. When repairing reinforced concrete do not damp reinforcing steel.

Mixing and application

Mix the primer using a drill and paddle mixer to form a creamy slurry. Using a brush or roller apply evenly over the surfaces ensuring total and uniform coverage taking care to avoid ponding. Only prime an area which can be covered by the rapid setting mortar/concrete within the working time of the primer.

When bedding building components such as bricks, brick slips, kerbs, paviours, prime the back of the component and the substrate.

When repairing concrete, apply two coats of primer to the dry reinforcing steel and a single coat to the damp concrete.

Note that the primer must not be allowed to dry. Apply the mortar/concrete to the wet/tacky primer. If the primer dries it must be thoroughly scratched and reapplied.



Ronacrete Rapid Primer

Rapid setting primer for fast setting cementitious products

Coverage	Ronacrete Rapid Primer is supplied in 2kg and 10kg packs. A 2kg pack will cover approximately 3-4m ² per coat and a 10kg pack will cover approximately 15-20m ² per coat.
Health and Safety	Refer to Safety Data Sheet.
Further Information	Reference should be made to the instructions contained in the technical data sheet for the mortar being applied.
Storage	Ronacrete Rapid Primer should be stored unopened between 5°C and 25°C in dry warehouse conditions and out of direct sunlight. In these conditions shelf life is approximately 6 months.
Site Attendance	When on site Ronacrete representatives are able, if asked, to give a general indication of the correct method of installing a Ronacrete product. It is important to bear in mind that Ronacrete Ltd is a manufacturer and not an application contractor and it is therefore the responsibility of the contractor and his employer to ensure he is aware of and implements the correct practices and procedures to ensure the correct installation of the product and that liability for its correct installation lies with the contractor and not with Ronacrete Ltd.

Ronacrete Rapid Primer

Rapid setting primer for fast setting cementitious products


Ronacrete Ltd, Flex Meadow, Harlow Essex, CM19 5TD, UK 13 0836-CPR-13/F047
BS EN 1504-4 Concrete Repair Structural bonding mortar to concrete
Product: Ronacrete Rapid Primer Reaction to Fire: A2-s1,d0 Release of Dangerous Substances: Refer to Safety Data Sheet

The information detailed in this leaflet is liable to modification from time to time in the light of experience and of normal product application, and before using, customers are advised to check with Ronacrete Ltd, quoting the reference number, that they possess the latest issue. Any person or company using the product without first making further enquiries as to the suitability of the product for the intended use does so at his own risk, and Ronacrete Ltd can accept no responsibility for the performance of the product, or for any loss or damage arising out of such use.

Screeds

RONL 698 Issue 2 16th July 2015



Ronac House, Flex Meadow, Harlow, Essex CM19 5TD, U.K.
Tel: +44 (0)1279 638700 www.ronacrete.co.uk technical@ronacrete.co.uk